

MODEL COMPARISON	B-SERIES	E-SERIES	M-SERIES	X-SERIES	Z-SERIES
NETWORKING					
Bridging Interface	Bypass Mode 1 Gbit Copper RJ45	Bypass Mode 1 Gbit Copper RJ45	Bypass Mode 1 Gbit Copper RJ45	Bypass Mode 1 Gbit Copper RJ45 or 1 Gbit Short-Run Fiber	Bypass Mode 10 Gbit Copper RJ45 or 10 Gbit Short-Run Fiber
Management Interface	10/100/1000 Copper RJ45	10/100/1000 Copper RJ45	10/100/1000 Copper RJ45	10/100/1000 Copper RJ45	10/100/1000 Copper RJ45
High Availability	Not Available	Not Available	Two Bridge Pairs Active/Standby Active/Active	Two Bridge Pairs Active/Standby Active/Active	Two Bridge Pairs Active/Standby Active/Active
Throughput Limits	1 Gigabit	1 Gigabit	1 Gigabit	2 Gigabits	12 Gigabits
HARDWARE					
Memory	8GB	8GB	16GB	16GB	24GB
Processor	Intel	Intel	Intel Xeon	Intel Xeon	Intel Xeon
Cores with Hyper Threading	4	8	8	8	20
Solid State Drive	No	No	Yes	Yes	Yes
Redundant Power Supplies	No	No	No	Yes	Yes
DIMENSIONS & POWER					
Appliance Dimensions	7.25W x 5.5D x 1.7H (in)	17W x 11.5D x 1.7H (in)	17W x 11.5D x 1.7H (in)	17W x 26.5D x 1.7H (in)	17W x 26.5D x 1.7H (in)
Mounting	Desktop	1U rack mount	1U rack mount	1U rack mount	1U rack mount
Shipping Weight	5 lbs.	15 lbs.	25 lbs.	35 lbs.	35 lbs.
AC Power	100-240 VAC	100-240 VAC	100-240 VAC	100-240 VAC	100-240 VAC