

REVISED 11.08.2017

MODEL COMPARISON	B-SERIES	E-SERIES	M-SERIES	X-SERIES	Z-SERIES
THREAT INDICATORS <i>IPS AND DOMAINS</i>					
Max Indicators	4 billion	4 billion	4 billion	4 billion	4 billion
Unique Indicators	120 million	120 million	120 million	120 million	120 million
NETWORKING					
Bridging Interface	Bypass Mode 1 Gbit Copper RJ45	Bypass Mode 1 Gbit Copper RJ45	Bypass Mode 1 Gbit Copper RJ45	Bypass Mode 1 Gbit Copper RJ45 or 1 Gbit Short-Run Fiber	Bypass Mode 10 Gbit Copper RJ45 or 10 Gbit Short-Run Fiber
Redundant Bridge Pairs	Not Available	Not Available	Two Bridge Pairs Active/Standby Active/Active	Two Bridge Pairs Active/Standby Active/Active	Two Bridge Pairs Active/Standby Active/Active
Management Interface	10/100/1000 Copper RJ45	10/100/1000 Copper RJ45	10/100/1000 Copper RJ45	10/100/1000 Copper RJ45	10/100/1000 Copper RJ45
High Availability	No	No	Yes	Yes	Yes
Throughput Limits	300 Mbps	600 Mbps	1 Gigabit	2 Gigabits	12 Gigabits
Concurrent Connections	500,000	500,000	1,000,000	2,000,000	2,000,000
HARDWARE					
Solid State Drive	No	No	Yes	Yes	Yes
Redundant Power Supplies	No	No	No	Yes	Yes
RAID	No	No	No	Yes	Yes
DIMENSIONS & POWER					
Appliance Dimensions	7.25W x 5.5D x 1.7H (in)	17W x 11.5D x 1.7H (in)	17W x 11.5D x 1.7H (in)	17W x 26.5D x 1.7H (in)	17W x 26.5D x 1.7H (in)
Mounting	Desktop	1U rack mount	1U rack mount	1U rack mount	1U rack mount
Shipping Weight	5 lbs.	15 lbs.	25 lbs.	35 lbs.	35 lbs.
AC Power	100-240 VAC	100-240 VAC	100-240 VAC	100-240 VAC	100-240 VAC